


Wecryl 210/-thix 10/-thix 20/-Wi Base resin for self-levelling mortar



Brief description

Wecryl 210 is a PMMA-based resin specifically designed for the requirements of Wecryl Self-Levelling Mortar.

It is used as a binder in Wecryl 233 Self-Levelling Mortar.

Material	Fast-reactive and flexibilised PMMA-based (polymethyl methacrylate) resin based on PMMA
Properties and advantages	<ul style="list-style-type: none">- Gives Wecryl 233 Self-Levelling Mortar its good application properties and flexibility- Fast-curing- Can also be applied at sub-zero temperatures- Solvent-free
Areas of application	Wecryl 210/-thix 10/-thix 20/-Wi is the base resin for Wecryl Self-Levelling Mortars (Wecryl 233/-thix 10/-thix 20/-Wi). It acts as binder in these products.
Differences between Wecryl 210/-thix 10/-thix 20/-Wi	<p>Wecryl 210 thix 10 and –thix 20 are variants of Wecryl 210 that are made more viscous / thixotropic to reduce excessive run-off when applied to sloping surfaces. Wecryl 210 thix 10 is recommended for gradients between 3 % and 10 %. Wecryl 210 thix 20 is optimised for gradients between 10 % and 20 %.</p> <p>Wecryl 210 Wi is a variant of Wecryl 210 that is optimised for application at low temperatures. The application and curing properties, in particular, were specifically modified for low-temperature use. We recommend that this product is applied at temperatures below 10 °C.</p>
Packaging	See product information sheet for Wecryl 233/-thix10/-thix20/-Wi Self-Levelling Mortar
Storage	Store products sealed in their original airtight container and in a cool, dry and frost-free place. Unopened products have a shelf life of at least 6 months. Direct sunlight on the containers should be avoided, including on site. After removing some of the contents, reseal the containers so they are airtight.
Technical data	Density: 1.00 g/cm ³
Further information	For further information please refer to the product information sheet for Wecryl 233/-thix10/-thix20/-Wi.
Information on safety and risks	Please refer to the safety data sheets for the products used.

Wecryl 210/-thix 10/-thix 20/-Wi Base resin for self-levelling mortar

General information

The above information, especially information about application of the products, is based on extensive development work as well as many years of experience and is provided to the best of our knowledge. However, the wide variety of requirements and conditions on site mean that it is necessary for the product to be tested to ensure that it is suitable for the intended purpose. Only the most recent version of the document is valid. We reserve the right to make changes to reflect advances in technology or improvements to our products.

Rev.: 18.03.2014