


Weplus 910

Anti-flow additive, powder



Brief description

The silica-based Weplus 910 allows the viscosity and thixotropy of liquid WestWood products to be increased. Consequently, the flow properties can be adapted to the ambient conditions.

Material

Silica-based, powdered thickening agent

Properties and advantages

- Immediately effective when stirred in

Areas of application

Weplus 910 is used to thicken (make thixotropic) WestWood PMMA resin products. This reduces any run-off of the resin products from sloping or vertical surfaces after application.

Packaging

1.00 kg in carton
5.00 kg in bag



Colours

Weplus 910 is white.

Storage

Store the product in the closed packaging and in a dry place. Unopened products have a shelf life of at least 12 months.

Consumption

Depending on the desired effect, up to 2 % anti-flow additive can be added to WestWood PMMA products (e.g. Wecryl 230). In the case of multi-component products, such as Wecryl 233 (consisting of Wecryl 210 and Wecryl 223), the quantity is always based on the resin component, so in this case on Wecryl 210.

Technical data

Density: 2.20 g/cm³
Apparent density: 30 - 150 kg/m³

Product application



Application equipment / tools

- Twin-paddle stirrer

Mixing

Slowly add the anti-flow additive to the liquid WestWood products while stirring and mix in thoroughly to achieve an even distribution. The thixotropic effect occurs immediately after stirring. Only then should Weplus Catalyst be added (see product information sheet for product used).

Information on safety and risks

Please refer to the safety data sheets for the products used.

Weplus 910

Anti-flow additive, powder

General information

The above information, especially information about application of the products, is based on extensive development work as well as many years of experience and is provided to the best of our knowledge. However, the wide variety of requirements and conditions on site mean that it is necessary for the product to be tested to ensure that it is suitable for the intended purpose. Only the most recent version of the document is valid. We reserve the right to make changes to reflect advances in technology or improvements to our products.

Rev.: 18.03.2014