

Product information sheet

## Weproof 304 /-thix Resin base for self-levelling mortar



## **Brief description**

Weproof 304 /-thix is a PMMA resin base specifically designed to meet the requirements of Weproof 527 /-thix.

Fast-reactive and flexibilised PMMA-based resin (PMMA = polymethyl Material

methacrylate).

Gives Weproof 527 its good application properties and flexibility **Properties and advantages** 

Fast-curing

Can also be applied at sub-zero temperatures

Solvent-free

Weproof 304 /-thix is the resin base for Weproof 527 /-thix. It acts as binder. **Applications** 

**Differences between** Weproof 304 and Weproof 304 thix

Weproof 304 thix is a modified version of Weproof 304 with increased viscosity to prevent excessive sagging on sloping surfaces.

Weproof 304 thix is recommended for gradients between 10% and 20%.

Pack size See product information sheet for Weproof 527 /-thix self-levelling mortar

Store products sealed in their original airtight container and in a cool, dry Storage

> and frost-free place. The unopened product has a shelf life of at least 6 months after delivery. Direct sunlight on the containers should be avoided, including on site. After removing some of the contents, reseal the containers

so they are airtight.

**Technical data** Density: 1.00 g/cm<sup>3</sup>

**Further information** For further information please refer to the product information sheet for

Weproof 527 /-thix

Information on safety and risks Please refer to the safety data sheets for the products used.

**General information** The above information, especially information about application of the

products, is based on extensive development work as well as many years of

experience and is provided to the best of our knowledge.

However, the wide variety of requirements and conditions on site mean that it is necessary for the product to be tested to ensure that it is suitable for the intended purpose. Only the most recent version of the document is valid. We reserve the right to make changes to reflect advances in

technology or improvements to our products.

Rev.: 01 February 2022

WestWood Liquid Technologies Limited · 31 Morris Road · Nuffield Industrial Estate · Poole · Dorset · BH17 0GG · United Kingdom Tel.: +44 800 808 5480 · info@westwood-uk.com · www.westwood-uk.com Page 1 of 1